

A white pickup truck is parked in front of a light-colored brick wall. On the bed of the truck, a large yellow and silver piece of equipment, identified as a penetrometer, is mounted. The truck has a spare tire mounted on the side of the bed. The background is a plain brick wall with two vertical green pipes.

TECOINSA

PENETROMETER

TP-05 LR

Dynamic automatic for DPSH test



TECOINSA

TÉCNICAS Y CONSTRUCCIONES INDUSTRIALES S.A.




TECOINSA

EQUIPOS DE SONDEO S.A.

Transport dimensions



- Length: 4439 mm
- High: 2079 mm
- Width: 1790 mm
- Weight: 2844 Kg



TECOINSA

TÉCNICAS Y CONSTRUCCIONES INDUSTRIALES S.A.




TECOINSA

EQUIPOS DE SONDEO S.A.

Penetrometer



- Beating hammer: 63,5 Kg
- DPSH fall height: 75 ± 2 cm
- Admissible rod: 1000 mm
- Electronic beat counter.
- Graduated ruler for penetration control.
- Set of dynamometric wrenches for torque control.
- Exceeds: ISO 22476-2:2005



TECOINSA

TÉCNICAS Y CONSTRUCCIONES INDUSTRIALES S.A.



TECOINSA


EQUIPOS DE SONDEO S.A.

Chassis



- Machine-mounted model LAND ROVER Defender 110 pick-up.
- Independent of the chassis frame of the vehicle, together with screws.
- 7,35 kW Yanmar diesel engine.
- Oil tank capacity:

55 l.



TECOINSA

TÉCNICAS Y CONSTRUCCIONES INDUSTRIALES S.A.



TECOINSA

EQUIPOS DE SONDEO S.A.

Complements



- With jaws for rod extraction.
- Centering rods.
- Includes drawer for tools and support rods.
- Centralized control panel.